

## Technical attributes

Type of machine	MINIPRESS M
Type of device	Table device
Control and drive	Electronic manual
Drilling and processing direction	Vertical drilling
Processing possibility	Drilling and component insertion
Drilling head assembly	Screw assembly
Type of connection	1-phase
Nominal voltage	1 x 230V
Operating power/frequency	1 x 230V, 50Hz
Nominal current	8.5
Motor performance	1,1
Frequency	50Hz
Safety certificate	CE declaration of conformity
Model	05
Length of base ruler	600mm
Dimension breakdown	Calibration from zero position: 11 13/16 Inch le, 11 13/16 Inch ri
Dimension breakdown	Calibration from zero position: 300 mm left, 300mm right
Type of chip removal	Chip exhaust
Maximum wood thickness	45mm (drilling only)
X-coordinate (parallel ruler)	300mm to left(MINUS),0mm(CENTREPOINT),300mm to right(PLUS)
Y-coordinate (right angle against ruler)	Vertical, from 0 to 70mm backwards
Z-coordinate (height)	45mm downwards (MINUS)
Processing of	Front fixings
Processing of	Hinges
Processing of	Mounting plates

Processing of	Connector
Drilling for:	System drilling
Net weight of assembly device	32
Mark of conformity on serial tag	CE
Dimensions (height/width/depth)	710mm, 610mm, 760mm